



**THE LONGEST COONARA AUSSIE
MADE WOODHEATER IS HERE**



PHOENIX  & NULLARBOR 



NULLARBOR ON TABLE & ON BENCH

The latest innovations to our woodheating range are the Nullarbor and Phoenix Linear Heaters. You will be mesmerised by the flames burning in front of you.

These stylish heaters boast a cast iron lined firebox to generate more heat, while the 3 speed fan will move this heat into your living space more effectively.

Where tradition meets innovation.

- Australian made and owned
- Glass size 1008mm wide 350mm high
- 3 speed fan included
- Standard Colour – charcoal
- Firebricks on base
- Durable cast iron lined box
- Removable Airslide Handle
- Removable Door Handle
- Table size 1120w x 523d x 370h
- 10 year firebox warranty





PHOENIX

The Phoenix Linear Woodheater will enhance any Australian home with its stylish looks and distinctive features.

This modern looking heater will turn a blank wall into the showpiece of your home as you become mesmerised by the flames burning in front of you.




NO FIREPLACE NECESSARY

Note: If the above heater is a minimum of 370mm off the floor, the hearth at the front can be 300mm.

With the Coonara Zero Clearance Box, you can install the Phoenix woodheater without the need of a conventional brick fireplace and chimney.

The Z Box allows you to install the Phoenix directly onto a floor using 50mm Hebel Blocks.


Detailed installation instructions, with clearances to combustible materials, are available from your Coonara dealer.



Timber framework, partially clad with 50mm Hebel Blocks



Zero Clearance Box positioned in framework on 50mm Hebel Blocks



Heater fitted to Zero Clearance Box with 600mm Hearth at front

WOODHEATER TECHNICAL SPECIFICATIONS



NULLARBOR NULLARBOR PHOENIX Z/C PHOENIX
ON TABLE **MASONRY F/P**

HEATING CAPACITY UP TO SQUARES *		30	30	30	30	
PARTICULATE EMISSIONS (G/KG)		0.7	0.7	0.7	0.7	
AVERAGE HEATING EFFICIENCY %		64	64	64	64	
AVERAGE PEAK POWER (Kw)	BURN TIMES: UP TO 9 HOURS ON LOW AND UP TO 5 HOURS HIGH	12.6	12.6	12.6	12.6	
FIRE BOX DIMENSIONS	HEIGHT (mm)	380	380	668	563	
	WIDTH (mm)	944	944	1250	1120	
	DEPTH (mm)	397	397	595 - Zero Box	523	
OVERALL DIMENSIONS (mm)	HEIGHT (mm)	563	933	646	646	
	WIDTH (mm)	1120	1120	1287	1287	
	DEPTH (mm)	523	523	543	543	
BACK OF HEATER TO CENTRE OF FLUE (mm)		202	202	182	182	
CLEARANCE TO COMBUSTIBLE MATERIALS (mm)	REAR SIDE CORNER	125 ⁺⁺ 475 N/A	125 ⁺ 475 N/A	25 25 Top 400	25 25 N/A	
	HEARTH DISTANCE (mm)	EITHER SIDE OF DOOR OPENING FRONT	210	210	210	210
			300	300	300/600	300/600
DESPATCH WEIGHT (kg)		250	290	305	250	

+ Rear clearance to be fitted with flue shield between the active flue and decromesh casing.

++ Refer to operating instructions manual P3.

* IMPORTANT: Heating areas provided are based on open plan living areas and 2.4 metre ceiling height.

Note: Lack of insulation, large window areas and cathedral ceilings reduce heating effectiveness.

Your Legendary Coonara dealer is:

All of the information contained in this brochure was correct at the time of printing, April 2024. However, the manufacturer reserves the right to make changes to design and specification without notice. You can confirm current designs, specifications, optional extras and financial details by consulting your nearest authorised Coonara dealer. Please note: Due to the nature of the printing process, colours may vary from those shown in this catalogue. Ask your dealer to show you a colour sample.



The Warmest Aussie Legend

14-18 Research Dve, Croydon Sth. 3136

Tel: (03) 9737 5300 coonara.com.au

A.B.N. 61 007 251 569